

TECHNICAL INFORMATION FOR **ECO IVVO**

TYPE:	Water solution of silicones with additives
DELIVERY SHAPE:	Bi-component water system
FEATURES AND USE:	ECO IVVO is used for the protection of wood from fire. It consists of two components that are successively applied to the wood. Protected wood does not burn, does not change the color and appearance. ECO IVVO is completely environmentally friendly (ecological) material. It is recommended to use ECO IVVO in combination with our products ECO IMPREGNIR L .
PREPARATION FOR APPLICATION:	ECO IVVO is applied in a delivered shape. The wood intended for protection should be dry and clean.
APPLICATION METHOD:	ECO IVVO component I is applied to the wood by spraying or coating using pneumatic sprayer, mop, sponge etc to material saturation. After drying of component I , component II is applied in the same way. To preserve the texture of wood the excess of component II has to be wiped with cotton cloth. The wood is protected after a 24-hour drying. ECO IVVO consumption: 0,10-0,30L/m ² .
SAFEGUARD MEASURES:	ECO IVVO is alkaline, so it is necessary to protect the face, hands and anything else not intended for conservation. Surfaces that are accidentally sprayed with this means can be washed with water. For professional use only!
PACKAGING:	2x200L Metal barrels and 2x10L plastic cans.
STORAGE:	ECO IVVO should be stored outdoors and indoors at temperatures above 4°C.
PRODUCT LIFETIME:	ECO IVVO can be kept in the original packaging for 12 (twelve) months.