

TECHNICAL INFORMATION FOR **ECO RECEPT 01mod**

TYPE: Acidic solution of surfactants

**DELIVERY
SHAPE:** Single component water system

**FEATURES
AND USE:** **ECO RECEPT 01mod** is used for the removal of limescale and other mineral impurities and routine maintenance of highly passable floor and other surfaces made of stone, artificial stone, terrazzo, ceramics, concrete, brick and similar materials, as well as all types of artificial polymeric floorings (linoleum, warm floors etc). The detergent is particularly suitable for the maintenance of sanitary facilities where it is used in combination with **ECO RECEPT 02mod**.

**PREPARATION FOR
APPLICATION:** **ECO RECEPT 01mod** is applied in a delivered shape or diluted with water in a volume ratio of 1:2 to 1:1 (detergent : water), depending on the type and degree of soiling on the area that needs to be cleaned. Shake well before use.

**APPLICATION
METHOD:** **ECO RECEPT 01mod** is applied to the surfaces by brush, sponge or spraying with pneumatic sprayer. After 5-15 minutes the surface is rinsed with water. The procedure is repeated until the desired result is achieved. Special attention should be paid when cleaning the limestone and similar materials to which concentrated detergent can cause damage.

**SAFEGUARD
MEASURES:** **ECO RECEPT 01mod** is acidic detergent, so it is necessary to use the appropriate safety equipment. In case the detergent comes in contact with exposed skin wash the spot with cold water. If accidentally gets into the eyes flush them immediately with cold water. Also, it is recommended to rinse eyes with a solution of sodium bicarbonate (baking soda). Surfaces accidentally sprayed with this detergent can be washed with water. For professional use only!

PACKAGING: 10L Plastic cans and 1L plastic bottles.

STORAGE: **ECO RECEPT 01mod** is stored outdoors and indoors at temperatures above 4°C.

**PRODUCT
LIFETIME:** **ECO RECEPT 01mod** can be kept in the original packaging for 6 (six) months.